# **AIDARY**

User manual
Heat Press Machine

**AP2361** 

# Introduction


A heat press machine is using temperature and pressure with a certain amount of time to transfer images on items, the transfer is permanently embedded into the product.

# **Package Contents**

1 x Heat Press Machine

1 x User Manual

# **Product Structure**



1. Emergency button	5. Hydraulic pump	
2. Power switch	6. Heat platen	
3. Intelligent LCD controller	7. Double working table	
4. Temperature display	8.Foot stand	

# 1.Printing Methods

- Make sure the power plug is well connected to the wall socket, then press the power switch to turn on.
- 2. Set the temperature and the time you want (See the temp&time setting sheet)
- 3. The buzzer will sound when the temperature reaches the setting temperature, place the object (e.g T-shirt) on press bed, and let the transfer paper upon the object.
- 4. Operate the controller and starts to transfer.
- The heat platen will lift up automatically when the scheduled time is up, then the transfer work is finished.
- If meet some emergent situation, press the emergency button, the plate will lift up immediately.

# 2. Recommended Setting for the Object

SURFACE	PRESS TIME	TEMPERATURE	PRESSURE	TIPS
Fiber/Fabric/Polyster material	35-40 seconds	180°C(400 F)	40 PSI (Medium)	With sublimation paper
Pure cotton material	20-25 seconds	165°C-170°C	40 PSI (Medium)	With transfer paper
Mouse pad	25-30 seconds	180°C(400 F)	40 PSI (Medium)	With sublimation paper
Metal card /Aluminium card	20-25 seconds	180°C(400 F)	40 PSI (Medium)	With sublimation paper

#### These are approximate datas FYI

### 3. Maintain Note:

- Different item will require different temperature and time setting because the materials or thickness is different.
- 2. This machine is not suitable for children to use or for food processing.
- 3. Please turn off the machine and unplug the power cord when the machine is not in use.
- 4. The heat plate will automatically cool down to the room temperature if the heat press stays non-use for more than 30 minutes.
- The heat-releasing fan will automatically starts when the temperature of heat plate reaches 80 °C (176 °F). It helps to reduce the temperature of electrical parts and prolong the service life of them

# 4. Troubleshooting:

#### No action after turn on the machine.

- 1. Check the plug whether it connects well or whether it is broken.
- 2. Check the fuse whether it has been burnt out.
- 3. Check the power switch or digital controller whether it is broken.

#### Indicating light is on but the display screen is black.

Check the 5 cable of railway transformer. The connection is poor if it is loose, just fix it. The transformer may be faulty if the cable is well connected just fix it.

#### The display screen is working well but the temperature is not heating up.

- Check if the indicating light of solid-state relay is on, if not, please check whether the relay
  or digital controller is broken.
- The heat platen still can't heating up if you already changed the new solid-state relay, please check whether the heat plate is faulty or the heat plate's power cable is loose, if so,it will need to change a new heatplate.

# The temperature is out of control: Set temperature $180^{\circ}C(356^{\circ}F)$ , but the actual temperature is above $200^{\circ}C(392^{\circ}F)$

- 1. It means the solid-state relay is broken, out of control, need to change a new relay.
- 2. Or the digital controller is faulty, need to change controller.

#### The print color is pale or faded image

The pressure is not high enough or The temperature is too low / pressing time is too short. Please adjust the pressure/ temperature or increase the heating time.

#### The print color is too Darkened, deep or blurred image

The temperature is too high / or pressing time is too long. Please adjust the temperature or reduce the heating time.

#### The print color is different/ partial transfer effect is not good enough

Pressing time is too short/ using poor quality transfer paper.

Please increase the heating time or use high quality transfer paper.

#### The transfer paper stick to the object after transfer

The temperature is too high / use poor quality printing transfer paper Please adjust the temperature or use high quality transfer paper.

# Fujian Aidary Applance Co.,Ltd



No.318,Bailong Area, Minhou,Fuzhou,Fujian, China.350018

www.aidary.com

https://www.facebook.com/heatpresscn

http://www.youtube.com/user/heatpresscn





